

5000 N. Highway 251 * Davis Junction, IL 61020 815.393.4600 * 815.393.3501 (fax) www.Skandialnc.com

60 DEGREE BUNSEN BURNER TEST FOR WIRE 14 CFR Part 25.869 (a)(4) Amdt 25-113 Appendix F Part I (a)(3)				Skandia, Inc. WO # 248533-12 Client PO 16978-N	
Pic Wire & Cable				Doc ID: 60DEG-269740	
N63 W22619 Main St.				Test Plan #	
P.O. Box 330				Rev	

Sussex WI 53089-0330 AIRCRAFT OR AIRCRAFT COMPONENT IDENTIFIC					
			ENT IDENTIFI	CATION	
Make: Stock		Model:N/A	Serial: N/A		Tail: N/A
Conditioning Room Data: Date In: 11/15/2012 Time In: 16:20 Date Out: 11/19/2012 Time Out: 13:28					
SPECIMEN MATERIALS					
Part No: E13426					
PIC Wire & Cable: USB Cable, White, Gauge 26, Ref. # 134055000001					
			<u> </u>		
Set	Flame Application	Flame Time	Burn Length		rip Flame Time
	(seconds)	(seconds)	(inches	s)	(seconds)
1	30	0.0	(0.9	0.0
2	30	0,0		1.0	0.0
3	30	0.0		1.0	0.0
	Average:	0.0	1.0		0.0
60 Degree Bursen Burner Test (30 seconds): Average Flame Time may not exceed 30 seconds.					
Average Burn Length may not exceed 3 inches. Average Drip Flame Time may not exceed 3 seconds after falling.					
Comments:					
9					
X Passed Failed					
CERTIFICATION: I certify that after testing these specimens, the above results were obtained in accordance with the					
procedures and equipment specified by Code of Federal Regulations Title 14 Part 25, revised as of January 1, 2004 and					
the Aircraft Materials Fire test Handbook dated April, 2000.					
Jennifer Paluzzi -FAA DER AMAL DA STORING 11/19/2012					
WITNESS WITNESS					DATE
- ff					UNIL