

A Division of the Angelus Corporation
 Ph (262) 246-0500 Fax (262) 246-0500 www.picwire.com
 PO Box 330 Sussex, WI 53089

Approved : 

Date : 07/25/18



Rev : 0

Distribution : USER

Uncontrolled if Printed

USB 3 Type B Plug Connector

(For PIC Cable P/N's USB3-2624 & USB3-2624-9)



PERFORMANCE

Voltage Rating 30 VAC (R.M.S.)
 Temperature Rating - 25° to + 80° C

CONNECTOR WEIGHT (Each)

0.144 ounces (4.08 grams)

RoHS COMPLIANT

Complies to RoHS Standards

APPLICABLE STANDARDS

USB 3.0 / 3.1

CONSTRUCTION

Materials:

Body	Steel
Contact	Phosphor Bronze
Insulator	Thermoplastic, UL 94V-0
Hood	ABS Resin - LSZH

Finish :

Contact	Gold over Nickel
Body	Nickel

INSTALLATION

Recommended Crimp Tool for crimping strain relief/cable shield is Tyco P/N 58433-1. Similar circular crimp tools acceptable.

Notes :

1) Two pieces of Raychem ATUM heat shrink, P/N's ATUM-8/2-0 (1 ea. X 0.5") & ATUM-4/1-0 (1 ea. X 1.0") provided with connector for strain relief & moisture protection.

2) Please refer to T-111095 Termination Instructions for stripping dimensions & instructions.