


A Division of the Angelus Corporation  
 Ph: (262) 246-0500 Fax: (262) 246-0450 www.picwire.com  
 W220 N1051 Sprindale Rd, Waukesha, WI 53089

Approved : *PFT*  
 Distribution : USER

Date : 03/11/21  
 Rev. 0  
 Uncontrolled if Printed

**RJ45 Plug Connector - Shielded Cat 6A  
 W/Strain Relief Sleeve**

(For conductors with an OD range of 0.044 to 0.048")



**PERFORMANCE**

Meets or Exceeds Category 6A ANSI/EIA 568-C.2  
 Performance Tuned to CAT 6A cables

Current/Voltage 1.5 Amps @ 30 VAC/42 VDC

Contact Resistance 10 milliOhms Max

**ENVIRONMENTAL**

Temperature Rating - 40° C to + 85° C

Insertion/Extraction 1000 Cycles

Flame Auto Extinguish UL 94-V0

**CONNECTOR WEIGHT (Each)**

0.12 ounces (3.40 grams)

**RoHS COMPLIANT**

Complies to RoHS Standards

**REQUIRED TOOLING (1)**

Crimp Tool P/N 111183

**CONSTRUCTION**

**Materials:**

Plug Housing	Polycarbonate
Contacts	Phosphor Bronze, 0.012" thick
Load Bar	Polycarbonate
Shielding	CDA-260 1/4 Hard Brass
Strain Relief	Thermoplastic Rubber

**Finish:**

Shield	Tin
Contacts	Gold

**Applicable Standards :** ANSI/TIA-1096-A  
 ANSI/TIA/EIA 568-C.2

**Notes :**

(1) Please refer to applicable T-111171 Termination Instruction Sheet for strip dimensions & instructions.