

PIC Wire & Cable

A Division of the Angelus Corporation

262-246-0500

Fax 262-246-0450

PO Box 330 Sussex, WI 53089

Connector Specification

P/N 190008

Approved




Date 01/15/03

Rev. 2 09/14/10

Distribution : USER

ARINC 600 Modified Size 1 Socket to TNC Jack Adapter



PERFORMANCE

Impedance	50 Ohms
Frequency Range	0 - 5 GHz
Voltage Rating	500 VRMS
Insulation Resistance	5000 Megohms

CONSTRUCTION

Materials:

Connector Body	Brass, ASTM-B16, Alloy UNS 36000, H02
Center Contact	Beryllium Copper, ASTM-B196, Alloy UNS C17300
Dielectric	TFE Fluorocarbon, ASTM-D1710, Type 1, Grade 1
Mounting Spring	Stainless Steel, ASTM 313
Retaining Ring	Stainless Steel, PH 15-7

Finish :

- Body	Gold
- Center Contact	Gold
- Spring, Ring	Passivated

Applicable Standards

ARINC 600
Mil-Std 348
MIL-PRF-39012

Connector Weight

.85 OUNCES (24.26 GRAMS)

RoHS Compliant

Complies to RoHS Standards

CONFIDENTIAL/PROPRIETARY: NEITHER THIS SPECIFICATION, NOR A PRODUCT OF THIS SPECIFICATION SHALL BE USED, COPIED, REPRODUCED OR DISCLOSED IN WHOLE OR IN PART WITHOUT THE WRITTEN CONSENT OF PIC WIRE & CABLE.