



PIC Wire & Cable	Connector Specification	P/N 190062
<i>A Division of the Angelus Corporation</i> Ph (262) 246-0500 Fax (262) 246-0450 www.picwire.com PO Box 330 Sussex, WI 53089	Approved : 	Date : 08/16/12
	Distribution : User	Rev. 3 : (05/13/15)
		Uncontrolled if Printed

RJ45 ISDN Plug Connector w/Protective Boot

(Connector has 4 cable conductor wire holes of 0.060")
 (Contacts @ Positions 3, 4, 5, and 6 only)



PERFORMANCE

Exceeds ANSI/TIA/EIA Cat 6
 Current / Voltage: 1.5 Amps @ 30 VAC / 42 VDC
 Contact Resistance: 10 milliOhms Max

ENVIRONMENTAL

Temperature Rating -40° C to +85° C
 Insertion / Extraction 1000 cycles

CONNECTOR WEIGHT

.18 ounces (4.99 grams)

RoHS COMPLIANT

Complies to RoHS Standards

REQUIRED TOOLING

Crimp Tool P/N 110340
 (Alternate) P/N 110274

CONSTRUCTION

Materials:
 Plug Housing Polycarbonate, Blue Tint, 94-V0
 Contacts Phosphor Bronze, .012" thk
 Rear Shield Copper Alloy
 Inner Ferrule Copper Alloy
 Strain Relief Boot Thermoplastic Rubber, 94-V0

Finish :
 Contacts Gold
 Rear Shield Tinned
 Inner Ferrule Tinned

APPLICABLE STANDARDS

ANSI/TIA-1096-A
 ANSI/TIA/EIA 568-C.2

Notes :
 1) Please refer to T-190062(-x) Termination Instruction sheet for strip dimensions & instructions.