

190052, 190054, & 190056 QUAD CONNECTOR™

PRODUCT BULLETIN

TIME, SPACE & MONEY SAVER

Four hermetically-sealed connections through one circular hole in the bulkhead. Available in TNC and BNC 50 Ohm, and BNC 75 Ohm types. TCAS/Mode S installations can use three panel holes instead of as many as twelve.



Installed QUAD Connector™



PIC has over 40 years of success in aircraft programs worldwide; let us help you find the best electronic cabling solution for your application.

Description	P/N	Characteristics
TNC, 4 Jacks (50 ohm)	190052	<ul style="list-style-type: none"> • (US Patent 6,835,093) RoHS Compliant • Frequency Range: 0-12GHZ • Voltage Rating: 500 VRMS • Insertion loss: .10 @ 1030 MHZ • Size: MIL-C-26482, Series 2, Size 24 Shell • Weight: 4.58 Ounces • Body & Finish Stainless/Passivated
BNC, 4 Jacks (75 ohm)	190054	
BNC, 4 Jacks (50 ohm)	190056	
TNC, 4 Jacks (75 ohm)	190060	

PIC
WIRE & CABLE

A Division of The Angelus Corporation

QUALITY TECHNOLOGY SERVICE

N53 W24747 S. Corporate Circle
P.O. Box 330, Sussex, WI 53089-0330

P • 262.246.0500 Toll Free • 800.742.3191
F • 262.246.0450

WWW.PICWIRE.COM

ISO 9001 • AS 9100



AIRCRAFT ELECTRONICS
ASSOCIATION
MEMBER

NBRA

v.011615