

# PRODUCT BULLETIN

## 190052, 190054, & 190056 QUAD CONNECTOR™

### TIME, SPACE & MONEY SAVER

Four hermetically-sealed connections through one circular hole in the bulkhead. Available in TNC and BNC 50 Ohm, and BNC 75 Ohm types. TCAS/Mode S installations can use three panel holes instead of as many as twelve.



Installed QUAD Connector™



*PIC has over 40 years of success in aircraft programs worldwide; let us help you find the best electronic cabling solution for your application.*

Description	P/N	Characteristics
<b>TNC, 4 Jacks (50 ohm)</b>	<b>190052</b>	<ul style="list-style-type: none"> <li>• (US Patent 6,835,093) RoHS Compliant</li> <li>• Frequency Range: 0-12GHZ</li> <li>• Voltage Rating: 500 VRMS</li> <li>• Insertion loss: .10 @ 1030 MHZ</li> <li>• Size: MIL-C-26482, Series 2, Size 24 Shell</li> <li>• Weight: 4.58 Ounces</li> <li>• Body &amp; Finish Stainless/Passivated</li> </ul>
<b>BNC, 4 Jacks (75 ohm)</b>	<b>190054</b>	
<b>BNC, 4 Jacks (50 ohm)</b>	<b>190056</b>	
<b>TNC, 4 Jacks (75 ohm)</b>	<b>190060</b>	