

Making Aircraft Quieter, Safer and More Comfortable. 5000 North Highway 251, Davis Junction, II. 61020 + 800 945 7135 | www.skandiainc.com

60 DEGREE BUNSEN BURNER TEST FOR WIRE 14 CFR Part 25.869 (a)(4) Amdt 25-113 Appendix F Part I (a)(3)				Skandia, Inc. WO # 280903-14 Client PO 18674-N	
Pic Wire & Cable N53 W24747 S. Corporate Circle OCT 3 1 2014				Doc ID: 60DEG-311783 Test Plan # Rev Project #	
Sussex WI 53089 USA				Technician Rickey Ryerson	
AIRCRAFT OR AIRCRAFT COMPONENT IDENTIFICATION					
Make: Stock		Model:N/A Serial: N		Α	Tail: N/A
Conditioning Room Data: Date In: 10/22/2014 Time In: 10:35 Date Out: 10/23/2014 Time Out: 11:14					
SPECIMEN MATERIALS					
Part No: \$22089					
Pic Wire & Cable: Coax, Clear					
Lot No 000138413					
	Flame Application	Flame Time	Burn	Length	Drip Flame Time
Set	(seconds)	(seconds)		ches)	(seconds)
4	30	0.0			,
1	30	0,0		1.4	0.0
2	30	0.0		1.5	0.0
3	30	0.0		1.3	0.0
	Average:	0.0		1.4	0.0
60 Degree Bunsen Burner Test (30 seconds): Average Flame Time may not exceed 30 seconds. Average Burn Length may not exceed 3 inches. Average Drip Flame Time may not exceed 3 seconds after falling.					
Comments:					
X Passed Failed					
CERTIFICATION: I certify that after testing these specimens, the above results were obtained in accordance with the procedures and equipment specified by Code of Federal Regulations Title 14 Part 25, revised as of January 1, 2004 and					
the Aircraft Materials Fire test Handbook dated April, 2000.					
10/23/2014					
Jan	WITNESS	and Julia	XXX		DATE