


A Division of the Angelus Corporation  
 Ph (262) 246-0500 Fax (262) 246-0450 www.picwire.com  
 PO Box 330 Sussex, WI 53089

Approved :   
 Distribution : USER

Date : 06/28/16  
 Rev. 3 (09/18/18)  
 Uncontrolled if Printed

**BNC Bulkhead Jack**  
 for UH44193



Recommended Jam Nut Torque - 35 to 40 in. lbs.

**PERFORMANCE**

Nominal Impedance : 50 Ohms  
 Frequency Range : 0 - 4 GHz  
 Voltage Rating : 500 V(rms)  
 Insulation Resistance : 5000 Megohms min.  
 Insertion Loss :  $0.12 \sqrt{F(\text{GHz})}$

**CONNECTOR WEIGHT (Each)**

0.72 ounces (20.53 grams)

**RoHS COMPLIANT**

Complies to RoHS Standards

**INSTALLATION****Center Contact**

M22520 / 1-01 Tool  
 Selector Dial Setting #8  
 Positioner : M22520 / 1-09

**Crimp Ferrule**

M22520 / 5-01 Tool  
 M22520 / 5-11 Die Set  
 (.213" A hex)

**CONSTRUCTION****Materials:**

Body	Brass, ASTM-B16, Alloy UNS 36000, H02
Cable Contact	Beryllium Copper, ASTM-B196, Alloy UNS C17300
Ferrule	Brass, ASTM-B16, Alloy UNS 36000, Dead Soft,
Dielectric	TFE Fluorocarbon, ASTM-D1710, Type 1, Grade 1
Gasket	Silicone Rubber

**Finish :**

Body, Ferrule	Nickel
Center Contact	Gold

**APPLICABLE STANDARDS**

MIL-STD 348, MIL-PRF-39012

**Notes :**

- 1) A 1.5" piece of Raychem ATUM heat shrink P/N ATUM-12/3-0 provided with connector for purpose of strain relief & moisture protection.
- 2) Please refer to T-1501XX Termination Instruction sheet for strip dimensions & instructions.