

**The following notes / flags apply to all cable assemblies on this drawing :**

1. All assembly work to be performed according to the A-10 assembly manual unless otherwise noted
2. XXXXX on label = PIC Wire & Cable serial number
3. Include appropriate test documentation with each shipment
4. Labels located 3 inches from back end of connector per PIC Work Instructions A-10 unless otherwise noted

**The following notes / flags apply to cables as noted on subsequent pages :**

5. All labels are white TMS type labels. Labels to be covered with clear heat shrink. Label all terminated ends only.
6. -XXX in P/N is equal to length of Assy in inches, -X in P/N is pin-out (-A = 568A, -B = 568B, -C = Cross-over). To order cable assembly specify 11012-4058-XXX-X. Example: 11012-4058-180-B = 180" cable Assy w/ 568B pin-out.
7. Cut length of cable is equal to assembly length specified plus .50". Example: Cut length of 180" cable assembly is 180.50".
8. Length tolerance for cable assemblies is + 2.0 / - 0"

REVISION HISTORY			
REV	DESCRIPTION	DATE	APPROVED
0	Initial Release	09/06/16	MCT

This drawing is proprietary to PIC Wire & Cable. No portion of this document may be reproduced or disclosed for any purpose without previous authorization from PIC Wire & Cable.

ACCEPTED:

\_\_\_\_\_

DATE:

\_\_\_\_\_





Sussex, WI 53089-0330  
 Phone 262-246-0500  
 Fax 262-246-0450

DESCRIPTION : Ethernet Cable Assembly

DRAWING NUMBER : 11012-4058

APPROVALS			DATE	SIZE	CAGE CODE	CUSTOMER: N/A	REV
DRAWN BY:	PFT	09/06/16	09/06/16	A	0BCW9		0
ENGINEER:	PFT	09/06/16	09/06/16				
ENG MGR:	MCT	09/06/16	09/06/16	SCALE : NONE	FILE: S:/...../11012-4058p1	SHEET: 1 OF 2	

- 5. All labels are white TMS type labels. Labels to be covered with clear heat shrink. Label all terminated ends only.
- 6. -XXX in P/N is equal to length of Assy in inches, -X in P/N is pin-out (-A = 568A, -B = 568B, -C = Cross-over). To order cable assembly specify 11012-4058-XXX-X.  
Example: 11012-4058-180-B = 180" cable Assy w/ 568B pin-out.
- 7. Cut length of cable is equal to assembly length specified plus .50". Example: Cut length of 180" cable assembly is 180.50".
- 8. Length tolerance for cable assemblies is + 2.0 / - 0"



RJ45 Wiring Configuration for 568A or 568B

Pin	568A Configuration	568B Configuration
1	White / Green	White / Orange
2	Green	Orange
3	White / Orange	White / Green
4	Blue	Blue
5	White / Blue	White / Blue
6	Orange	Green
7	White / Brown	White / Brown
8	Brown	Brown

Top View


RJ45 Cross-over Wiring Configuration

Pin	568A @ End A	568B @ End B
1	White / Green	White / Orange
2	Green	Orange
3	White / Orange	White / Green
4	Blue	Blue
5	White / Blue	White / Blue
6	Orange	Green
7	White / Brown	White / Brown
8	Brown	Brown

Top View

This drawing is proprietary to PIC Wire & Cable. No portion of this document may be reproduced or disclosed for any purpose without previous authorization from PIC Wire & Cable.

Test continuity and shorts



Sussex, WI 53089-0330  
Phone 262-246-0500 Fax 262-246-0450

DESCRIPTION : Ethernet Cable Assembly  
DRAWING NUMBER : 11012-4058

SIZE A	CAGE CODE OBCW9	CUSTOMER: N/A	REV 0
--------	-----------------	---------------	-------

SCALE : NONE FILE: S:/...../11012-4058p2 SHEET: 2 OF 2